



| PIN NO. | SIGNAL |
|---------|--------|
| 1 | VDD |
| 2 | C86 |
| 3 | VSS |
| 4 | V0 |
| 5 | V1 |
| 6 | V2 |
| 7 | V3 |
| 8 | V4 |
| 9 | CAP2- |
| 10 | CAP2+ |
| 11 | CAP1+ |
| 12 | CAP1- |
| 13 | CAP3+ |
| 14 | VOUT |
| 15 | VSS |
| 16 | D7 |
| 17 | D6 |
| 18 | D5 |
| 19 | D4 |
| 20 | D3 |
| 21 | D2 |
| 22 | D1 |
| 23 | D0 |
| 24 | /RD |
| 25 | /WR |
| 26 | A0 |
| 27 | /RES |
| 28 | /CS1 |

| | | |
|----------------------|-------------------|----------|
| 1. DISPLAY TYPE | PSIV/NEGATIVE | Approve |
| 2. VIEWING DIRECTION | 6 O'CLOCK | |
| 3. POLARIZER MODE | TRANSRECTIVE | Checked |
| 4. DRIVE METHOD | 1/65DUTY 1/9 BIAS | |
| 5. OPERATIVE VOLTAGE | 8.0V | Drawn |
| 6. OPERATIVE TEMP. | 0° C TO 50° C | |
| 7. STORAGE TEMP. | -10° C TO 60° C | Approved |
| 8. CONNECTOR | COG/S17565R | |

深圳市飞格达电子有限公司
 SHENZHEN FEIGEDA ELECTRONIC CO.,LTD
 Dwg.No **FGD12864C-7565R-28P4**

| | |
|--------------------|------------|
| Unmarked Tolerance | ±0.2 |
| Unit | mm |
| Scale | |
| Date | 2006/11/10 |
| Page | 1/1 |
| | |
| | |